

**CF MEDIAPLAYER MPL027PS-X HD 1080P****TECHNICAL DATA**

CF-Card, SD-Card, USB-Update, 40Mbs data rate, Multi zone function 3D video playback

Video out:	Video (Chinch), HDMI, VGA (D-Sub-15pol.), Y.Pb.Pr. über VGA Adapter
Audio out:	Stereo 3,5mm plug, HDMI
Resolution:	
Video:	PAL, NTSC, HD Y.Pb.Pr.: 480P/720P/1080i NTSC (60Hz) 576P/720P/1080i PAL (50Hz) HDMI: 480i/480P/720P/1080i/1080P (60Hz) 576i/576P/720P/1080i/1080P (50Hz) VGA: 640x480/800x600/1024x768/1280x1024/1360x768/1366x768
Format:	HD WMV9, MPEG2, MPEG4, MPEG @HD, H-264, MOV-H264, PEG PNG
Multizone Screen:	Standard: 1x Movie 720P, 1x Text Ticker, 1x PNG Expanded: 1x Video, 1x Date/Time, 1x Ticker, 3x BMP Free configurable layout via XML
Control:	Auto-Power On, Repeat all format (Movies + JPEG) RS-232 interface ASCII (Play, Stop, Movie Selection etc.) http > Network control, IR Remote control
Miscellaneous:	Log File (Movie Nr., Time, Date), Export of Player settings on CF Card, FTP Server, Support NTP Network (G.M.T) Timer
OSD Menu:	English
Memory Card:	CF Type I/II up to 16GB > 150
Package content:	Power supply 110/220V AC / 12V DC/1,5A IR remote control 1x Audio cable (2x Chinch) 1x Video cable (3x Chinch) 1x CD ROM with playout software, License free up to 5 players Safety bow for CF-Card-Slot
Accessories-optional:	Button box BB16 for selection up to 16 movies / JPEG (Control via RS232-Port) PHR motion sensor VESA mount
Dimensions:	267(B) x 29(H) x 136(W) mm
Weight:	850g
Power supply:	Universal power supply 110/220V AC / 12V DC/1,5A

## CF MEDIAPLAYER MPL027PS-X 8 HD1080P



### TECHNICAL DATA

CF-Card, SD-Card, USB Update, 40Mbps Data rate, Multi zone function 3D,  
Video Playback Button Interface for 8 LED buttons

Video/Audio out:	HDMI
Resolution:	HDMI: 480i/480P/720P/1080i/1080P (60Hz) 576i/576P/720P/1080i/1080P (50Hz)
Video Formats:	HD WMV9 MPEG2, MPEG4 MPEG @HD, H-264, MOV-H264 JPEG PNG
Multizone Screen:	Version A: 1x Movie 720P, 1x Text Ticker, 1x PNG, Version B: 1x Video, 1x Date/Time, 1x Ticker, 3x BMP Free design via XML
Control:	Programmable Timer for Auto-Power On / Off, RS-232 Interface RX / TX 19200 Baud http > Remote Control IR Remote Control
Miscellaneous:	Log File (Movie No / Time / Date) Configuration File Export with CF Card, FTP Server Support NTP Network (G.M.T) Timer
OSD Menu:	English
Memory Card:	CF Type I/II up to 16GB/ > 150-fach
Package Content:	Power Supply 110/220V AC / 12V DC/1,5A IR Remote Control Protective Cover for CF-Card-Slot
Accessories:	PHR motion sensor (optional) VESA mount
Dimension:	267(B) x 29(H) x 136(T) mm
Weight:	850g

## CF MEDIAPLAYER MPLO28H-B6 HD



### TECHNICAL DATA

Video out:	HDMI
Audio out:	Stereo 3,5mm jack
Resolution:	PAL / NTSC/ 480i / 576i / 480p / 576p / 720p / 1080i / 1080P 4:3 / 16:9
Media Format:	Music, JPG, MPEG2, MPEG4, DivX, VOB, MOV,
Button Control:	6-lighted (LED) Buttons with multi functions: Modus: Function Button 1 > 6 Play/ Pause, Stop, Next, Prev, Volume + / - Buttons not illuminated. Modus: Number Button 1 > 6 File selection 1 to 6, File 00 > Loop LED Lightning (only Number Modus): Modus Running: All Buttons blinking until one file is selected, than only the selected button is illuminated. Modus Static: All buttons dark, if one file is selected, the LED gives Light until the file is finished.
Functions:	Auto-Power On, Repeat, Movies or JPEG or Audio, NOT MIXED
Slideshow:	3/5/10/30/60 Sec. / 5 Min.
Transition:	Full screen Random Function
Timer:	Daily, Weekly, 3 x On / Off per day.,
OSD Menu:	Multilanguage
Memory Card:	SDHC Card max. 32GB, USB Stick,
Package contents:	Power Supply, Remote Control, 6 x LED Buttons, Red, Cable 50cm,
Dimension:	170 x 110 x 29mm
Weight:	500 g
Power Consumption:	5V DC / 1,5A

## CF MEDIAPLAYER MPL031HD



### TECHNISCHE DATEN

Video out:	HDMI, VGA,
Audio out:	3,5 mm Stereo Jack
Resolution:	HDMI / DVI (DVI with adapter HDMI> DVI) 480i, 576i, 480P, 576P, 720P, 1080i, 1080P 640x480, 800x600, 1024x768, 1280x720, 1280x768, 1280x1024, 1360x768, 1366x768, 1400x1050, 1440x900, 1600x900, 1600x1200, 1680x1050, 1920x540, 1920x1080, 1920x1200, VGA: 640x480, 800x600, 1024x768, 1280x720, 1280x768, 1280x1024, 1360x768, 1366x768, 1400x1050, 1440x900, 1600x900, 1600x1200, 1680x1050, 1920x540, 1920x1080, 1920x1200,
Standard:	PAL / NTSC
Video format:	MPEG1 /2,MPEG4.2 ,MPEG4.10 (H264),WMV9,SMPTE421M(VC-1)
Foto:	JPEG, PNG bis zu 4096x4096
Audio format:	MPEG1 Layer I, II, III,MPEG4 -ACC-LC,WMA9,WMA9-Pro,
Memory:	SD-Card 512MB>32GBFAT32,USB-Stick,
Functions:	Seamless Repeat<0,1SekwithWMVFormat Auto Power On, Timer Function, Multi synchronic playback up to 254Player, Scrolling text,4 different colors, background, position selectable Different operation mode: Standby, Repeat, Menu, Continue Schedule / Playlist
Control:	RS232 Standard Interface (Hex) LAN / UPD Remote Control
LAN:	RJ-45 10/100 Mbps Static / dynamic IP
OSD Menu:	English
Dimension:	174 (W) x 33,1 (H) x 127,7 (D) mm
Weight:	300 g
Power consumption:	DC12V/ 0,8A
Package contents:	Power adaptor 110-220V AC / 12V / 2A DC IR-Remote control
Optional accessories:	Button Box BB24